

# RAGE™ Bypass Plungers

High efficiency and continuous flow



## UNIBODY™ Bypass Plungers

### Application

High Flowrate wells that require minimal close time and/or constant cycling for optimal liquid removal.

**Tubing Size 2 3/8 and 2 7/8**

### Body Area

- + Solid ONE piece design
- + Alloy or stainless steel
- + Exceptional “crimple” fastening method
- + Incorporated wear rings
- + Centralized fluted design (other options available)
- + Multitude of slot sizes available for various production rates

US PATENT #9,677,389

### RAGE™ BYPASS PLUNGERS

- + **Shorty:** Deviation and low volume.
- + **Standard Groove:** Low deviation/high volume wells. Paraffin control.
- + **Fluted:** High deviation/high volume wells. Used for paraffin control and for more consistent plunger wear.
- + **Single Pad:** Better seal/deviated wells.
- + **Dual Pad:** Best seal/low volume wells.
- + **Shuttle™:** For high flowrates and/or wells that produce sand and/or solids.
- + **Titanium Sliding Sleeve:** Used for deviated and more gassy wells. Does not require a stinger rod for operation. Used for higher rate wells as well.
- + **Standard Sliding Sleeve:** 4-port adjustable/flexible, port selection varies based on your needs, you can plug a port as the wells production changes
- + **Padded Sliding Sleeve:** Fast falling plunger with no shifter rod required. Provides all the benefits of sliding sleeve options with the sealing efficiency of a dual pad. Unique pad design allows for maximum sealing efficiency and increased longevity, patented fastening method allows for no pins or welds throughout the plunger.

### UNIBODY™ Bypass Plungers



### Other Bypass Plungers

